


DIGITAL ASTRO TIMERS

paladin 173 113 easy



ZUBEHÖR



Save'n carry 2.0

Overview

- Time switch digital astro
- Flush-mounted fitting
- 1 channel
- Daily and weekly program
- Astro program
- Economical night program
- Extra switching times
- 56 memory locations
- 10 years battery-reserve
- Minimum interval 1 min
- Switching capacity 10 A per channel
- Permanent by date / holiday function
- Manual permanent mode
- Manual override
- Automatic sorting of switching times on readout
- Unrestricted block programming
- Fully automatic daylight saving time
- Elapsed time and pulse counter
- Security by PIN-Code
- Text based menu
- Easy handling
- Data security through non-volatile memory
- Optimized Quartz accuracy for typical ambient conditions in standard installations
- Illuminated display
- NFC programming (ISO 15693 Standard)

Highlights

- Astro program
- Complete switching program of the present day at a glance
- Large, clear and illuminated display with one text line
- Easy handling
- Quick and intuitive programming
- Can be programmed with supply disconnected
- Data security through non-volatile memory
- Programmable with smartphone via NFC (free Save'n carry App)
- Ideal for modern lamps [LED, CFL, etc.]

App to program the time switch

Save 'n carry 2.0 (Google Play Store)
<https://play.google.com/store/apps/details?id=de.hugomueller.ProjectApp>

Save'n carry 2.0 (App Store)
<https://apps.apple.com/de/app/saven-carry-2-0/id6444333521>

Order numbers

■ **paladin**
 173 113 easy 1 channel version

DIGITAL ASTRO TIMERS

paladin 173 113 easy

Order information

	Voltage	EAN	Art. No.
173 113 easy	230 V 50-60 Hz	4022709233219	23321
Other supply voltage versions on request			

Technical data

Supply voltages	230 V, 50-60 Hz
Power consumption (real power)	0,6–0,8 W (depending on the switching status)
Channel (potential-free)	Change-over
Contact material	AgSnO ₂
Switching capacity resistive load:	10 A / 250 V~ at cosφ=1
inductive load:	10 A at cosφ=0,6
Min. switching power	1.000 mW (10 V / 10 mA)
Max. starting current	50 A max. 20 ms
Filament Lamp, Halogen Lamp	2.000 W
Fluorescent Lamp uncompensated	1.000 VA
Fluorescent Lamp series compensated	1.000 VA
Fluorescent Lamp parallel compensated	550 VA
LED (230 V~) / CFL	200 W
Switching functions	
Astro:	ON/OFF
Night:	ON/OFF
Extra:	ON/OFF
Permanent	ON/OFF
Offset Astro switching time	+/-90min.
Memory locations	56
Minimum interval	1 Min.
Time base	Quartz
Quartz accuracy (at 20°C)	±0,5 Sec./day (Quartz accuracy optimized for typical ambient conditions)
Power back-up (at 20°C)	approx. 10 years (depends on the Lithium-battery life)
Program security	unlimited
Display	illuminated LCD
Permitted ambient temperature	–30°...+55°C
Housing	self-extinguishing thermoplastic
Colour: cover frame adapter frame cover plate	Polarwhite (similar to RAL 9010)
Mounting	Flush-mounting
Type of connection	Screw terminals (pull-up type)
Type of protection	IP 20 to DIN EN 60529
Class of protection	II when installed according to regulations
Mode of operation (DIN EN 60730-1) (DIN EN 60730-2-7)	1 BSTU
Degree of contamination (DIN EN 60730-1)	2
Rated surge voltage (DIN EN 60730-1)	4 kV

Rights to technical amendments reserved / Technische Änderungen vorbehalten
Droits de modifications techniques réservés / Suscettibile di errori e modifiche

