

## TWILIGHT SWITCHES

paladin 922 000



### Overview

- Analogue twilight switch
- Wall mounting
- Adjustable 2 to 2.000 lux
- Time delay approx. 1 min. before switching takes place
- LED-adjustment aid, without delay
- Fitted for high lamp loads
- Double line entrance from below or through the housings rear pane

### Order numbers

■ **paladin**

922 000

1 channel

# TWILIGHT SWITCHES

## paladin 922 000

### Order information

	Voltage	EAN	Art. No.
<b>922 000</b>	230 V 50-60 Hz	4011732012663	01266

### Technical data

Supply voltages	230 V, 50–60 Hz
Power consumption	6 VA
Channel	Normally Open, 10 A 250 V AC
Switching capacity	
resistive load::	10 A / 250 V~ at $\cos\phi=1$
inductive load:	2 A at $\cos\phi=0,6$
Max. switching capacity	1.200 W
Filament Lamp, Halogen Lamp	1.200 W
LED	100 W
Lux range	2–2.000 Lux
Switching delay	approx. 20...120 sek.
Permitted ambient temperature	–35...+60 °C
Type of protection	IP 54
Dimensions	111 x 83 x 43 mm
Mounting	Wall
Hysteresis	approx. 30 %

Rights to technical amendments reserved / Technische Änderungen vorbehalten  
Droits de modifications techniques réservés / Suscettibile di errori e modifiche

