

RF SWITCHING ACTUATORS

Switching actuator 1-channel paladin 672 730 rf



Overview

- Switching actuator 1-channel
- Functions: Switching (on / off), Timer (3 sec. - 10 min.)
- Breaking capacity: 250 V / 16 A
- Adjustable Timer from 3 seconds to 10 minutes
- Additional input for wired push button
- RF-repeater function included
- DIN-rail mounting
- Protection class IP 20
- KNX-RF compatible

Order numbers

■ **paladin**

672 730 rf Switching actuator
1-channel

RF SWITCHING ACTUATORS

Switching actuator 1-channel paladin 672 730 rf

Technical data

Supply voltage	230 V~ 50 Hz
Power consumption	35 mA
Breaking capacity	16 A 250 V (cos φ=1)
Transmission type	Codified transmission in 868,4 MHz with ERP>8 mW and a coverage of 100 m (in the free field)
Operating modes	Switching (ON / OFF) Timer
Timer delay	00:03 to 10:00 mm:ss
KNX-RF compatible commands	CH_Light_Actuator_Scene (0103h)
Permitted ambient temperature	-10°...+45°C
Dimensions	1 module wide (17,5 mm)
Mounting	35 mm DIN-rail
Connection type	Screw-type terminal
Protection degree	IP 20

Rights to technical amendments reserved / Technische Änderungen vorbehalten
Droits de modifications techniques réservés / Suscettibile di errori e modifiche

