

WIRELESS DIMMERS

Universal dimmer RLC LED paladin 673 830 rf



Overview

- Universal dimmer for R,L,C and LED lamps
- Max. load 250 W (halogen lamps with electronic transformer)
- Minimum dimming-value adjustable
- For leading or trailing edge dimming
- Additional input for wired push button
- RF-repeater function included
- Compact housing
- Flush-mounted fitting
- Protection class IP 20
- KNX-RF compatible

Order numbers

■ **paladin**

673 830 rf

Universal dimmer for
RLC & LED lamps

WIRELESS DIMMERS

Universal dimmer RLC LED paladin 673 830 rf

Technical data

Supply voltage	230 V ~50/60 Hz
Power consumption	2,6 VA
Switching capacity	Halogen lamps w. electronic transformer: up to 250 W Halogen lamps with inductive transformer: up to 200 W LED with leading edge: 4 W...100 W LED with trailing edge: 4 W...250 W
Transmission type	Codified transmission in 868,4 MHz with ERP>8 mW and a coverage of 100 m (in the free field)
Switching functions	Switching (ON / OFF) Dimming Set dimming value
Permitted ambient temperature	0°C...+40°C
Dimensions	46 x 46 x 30 mm
Mounting	Flush-mounting
Connection type	Screw-type terminal
Protection class	IP 20

Rights to technical amendments reserved / Technische Änderungen vorbehalten
Droits de modifications techniques réservés / Suscettibile di errori e modifich

