

WIRELESS DIMMERS

Dimmer LED RGB strip paladin 674 830 rf



Overview

- Dimmer for building automation
- to dim RGB LED strips (12V ... 48V DC)
- Ideal in combination with sender paladin 673 010 rf
- KNX-RF compatible
- RF-repeater function included
- Compact housing
- Recessed ceiling mounting
- Protection class IP 20

Order numbers

■ **paladin**

674 830 rf

Dimmer LED RGB strip

WIRELESS DIMMERS

Dimmer LED RGB strip paladin 674 830 rf

Technical data

Power supply	12V...48VDC
Current consumption	<12mA
Load	LED strips 12VDC ~ 48VDC
Max. load	5A per channel
Channels	3 output channels (4 working channels)
Functions	Dimming Signal amplifier (repeater) KNX-RF
Transmission type	Codified transmission Frequency 868,4 MHz Range max. 100 m
Working temperature	0°C...+40°C
Dimensions	105 x 50 x 12 mm
Mounting	Recessed ceiling mounting
Connection type	Screw-type terminal
Protection class	IP 20
Compatible with	676 010 rf 673 010 rf 670 010 rf

Rights to technical amendments reserved / Technische Änderungen vorbehalten
Droits de modifications techniques réservés / Suscettibile di errori e modifiche

