

## WIRELESS SENSORS AND TRANSMITTER

Door-/window contact sensor paladin 676 410 rf



### Overview

- Wireless door- / window contact sensor
- Transmission of open / closed status via RF
- Battery operated (battery lifetime ~ 12 years)
- Compact housing
- Wall mounting
- Protection degree IP 20
- KNX-RF compatible

### Order numbers

■ **paladin**

676 410 rf

Door-/ window contact  
sensor battery operated

# WIRELESS SENSORS AND TRANSMITTER

## Door-/window contact sensor paladin 676 410 rf

### Technical data

Power supply	Battery operated 2 x 3 V CR2032 (included)
Battery lifetime	~ 12 years
Transmission type	Codified transmission in 868,4 MHz with ERP>8 mW and a coverage of 100 m (in the free field)
Compatible KNX-RF Commands	CH_Window_Door_Contact_Basic (0023h) CH_Battery_Status (0021h)
Permitted ambient temperature	-10° C...+70° C
Dimensions	Sender: 78 x 28 x 23 mm Magnet: 60 x 16 x 12 mm
Mounting	Wall-mounting
Protection degree	IP 20

Rights to technical amendments reserved / Technische Änderungen vorbehalten  
Droits de modifications techniques réservés / Suscettibile di errori e modifiche

