

ELAPSED TIME COUNTERS

müller BW 30 - BG 30



Retaining clip for Bx
30

Overview

- Front panel 53 x 28 mm
- Integral locking spring
- With universal connections
- Touch proof connections to VBG4
- Mounting aperture: 50 x 25 mm

Supply voltage versions

- see technical data

Order numbers

■ müller	
BW 30.18	AC / Front 53x28mm
BG 30.18	DC / Front 53x28mm

ELAPSED TIME COUNTERS

müller BW 30 - BG 30

Order information

	Voltage	EAN	Art. No.
BW 30.18	230 V 50 Hz	4022709203069	20306
BG 30.18	12-48 V DC	4022709200402	20040

Other supply voltage versions on request

Technical data BW 30.18 Alternating current

Voltage tolerance	±15%
Power consumption (real power)	0,11 W
Counter capacity	99.999 h.
Accuracy of reading	0,01 h.
Numeral height	4,4 mm
Numeral colour	white, decimal figures red
Operation indicator	fast-running wheel
Permitted ambient temperature	-15...+50 °C
Housing	self-extinguishing thermoplastic
Mounting	Panel
Type of connection	Universal: Screw, soldered and 6.3 x 0.8 mm AMP plug-type connections
Type of protection (DIN EN 60529)	Front IP 65
Class of protection	II when fitted in accordance with regulations

Technical data BG 30.18 Direct current

Supply voltages (Please state when ordering)	12-48 V DC
Special voltages	5-24 V 100-300 V DC
Other voltages	on request
Voltage tolerance	±10%
Power consumption (real power)	approx. 20 mW at 12 V DC
Counter capacity	99.999 h.
Accuracy of reading	0,1 h.
Numeral height	4,4 mm
Numeral colour	white, decimal figures red
Operation indicator	LED
Permitted ambient temperature	-10°...+50°C
Housing	self-extinguishing thermoplastic
Mounting	Panel
Type of connection	Universal: Screw, soldered and 6.3 x 0.8 mm AMP plug-type connections
Type of protection (DIN EN 60529)	Front IP 65
Class of protection	III (up to 48 V DC)

Rights to technical amendments reserved / Technische Änderungen vorbehalten
Droits de modifications techniques réservés / Suscettibile di errori e modifiche

