

## ELAPSED TIME COUNTERS

müller BW 30 - BG 30



Retaining clip for Bx  
30

### Overview

- Front panel 53 x 28mm
- Integral locking spring
- With universal connections
- Touch proof connections to VBG4
- Mounting aperture: 50 x 25 mm

### Supply voltage versions

- see technical data

### Order numbers

#### ■ müller

BW 30.18

AC / Front 53x28mm

BG 30.18

DC / Front 53x28mm

# ELAPSED TIME COUNTERS

## müller BW 30 - BG 30

### Order information

	Voltage	EAN	Art. No.
<b>BW 30.18</b>	230 V 50 Hz	4022709203069	20306
<b>BG 30.18</b>	12-48 V DC	4022709200402	20040

Other supply voltage versions on request

### Technical data BW 30.18 Alternating current

Voltage tolerance	±15%
Power consumption (real power)	0,11 W
Counter capacity	99.999 h.
Accuracy of reading	0,01 h.
Numeral height	4,4 mm
Numeral colour	white, decimal figures red
Operation indicator	fast-running wheel
Permitted ambient temperature	-15...+50 °C
Housing	self-extinguishing thermoplastic
Mounting	Panel
Type of connection	Universal: Screw, soldered and 6.3 x 0.8 mm AMP plug-type connections
Type of protection (DIN EN 60529)	Front IP 65
Class of protection	II when fitted in accordance with regulations

### Technical data BG 30.18 Direct current

Supply voltages (Please state when ordering)	12-48 V DC
Special voltages	5-24 V 100-300 V DC
Other voltages	on request
Voltage tolerance	±10%
Power consumption (real power)	approx. 20 mW at 12 V DC
Counter capacity	99.999 h.
Accuracy of reading	0,1 h.
Numeral height	4,4 mm
Numeral colour	white, decimal figures red
Operation indicator	LED
Permitted ambient temperature	-10°...+50°C
Housing	self-extinguishing thermoplastic
Mounting	Panel
Type of connection	Universal: Screw, soldered and 6.3 x 0.8 mm AMP plug-type connections
Type of protection (DIN EN 60529)	Front IP 65
Class of protection	III (up to 48 V DC)

Rights to technical amendments reserved / Technische Änderungen vorbehalten  
Droits de modifications techniques réservés / Suscettibile di errori e modifiche

