

DIMMERS

paladin 879 443 knx



Overview

- Dimming actuator / DALI gateway for DALI drivers / ballasts (ECG's)
- 3 channels, control up to 64 devices per channel, max. 128 devices in total
- Unidirectional and broadcast communication (no separate addressing)
- 1 group per channel
- Integrated overload-, short-circuit- and overheat protection.
- Memoryfunction (of the last dimming value)
- Control knob for dimming function test - even without KNX-bus connected
- Panic function
- Different functions and parameters can be enabled parameterized by the ETS:
 - staircase lightning timer with warning function
 - dimming speed
 - Up to 5 Scenes can be stored / called up
 - cycle function
 - Soft turn ON / OFF
 - etc.

Order numbers

■ **paladin**

879 443 knx DALI-dimmer
3-channel

DIMMERS

paladin 879 443 knx

Order information

	EAN	Art. No.
879 443 knx	4022709239273	23927

Technical data

Supply voltage	230 V, 50 Hz
Supply voltage bus	via KNX bus voltage
Bus current	< 10 mA
Compatible load type	DALI drivers DALI lamps DALI ECG's
Maximum number of controlled devices	64 per channel 128 in total
Number of outputs	3
Bus system	KNX
Application software	ETS4 or later
Permitted ambient temperature	-5...+45 °C
Storage temperature	-30...+70 °C
Dimensions	90 x 87,5 x 65 mm
Mounting	35 mm DIN-rail
Connection type	KNX-bus connector screw terminals (power supply / lamps)
Type of protection	IP 20 (DIN EN 60529)

Rights to technical amendments reserved / Technische Änderungen vorbehalten
Droits de modifications techniques réservés / Suscettibile di errori e modifiche

