

0-10V SENSORS

Air quality sensors GS 40.00 pro



Accessories



Back part for surface wiring
200.004

Overview

- Detection of air quality (CO₂-concentration, rel. humidity, temperature)
- CO₂-sensor (Measuring range 390...5.000 ppm)
- CO₂-value is atmospheric pressure compensated
- Sensors for CO₂-, temperature, humidity and atmospheric pressure measurement
- Temperature sensor (Measuring range 0...+50 °C)
- Humidity sensor (Measuring range 0...100% rel. humidity)
- 3 control outputs (0-10 V) for measured values of CO₂ concentration, rel. humidity and temperature
- Easy installation and mounting
- Modern and planar design

Information about CO₂ and Covid-19

- Every person is emitting CO₂ and aerosols e.g. during breathing. Today **aerosols are claimed to be one of the transmission ways of SARS-CoV-2**. CO₂-concentrations can be measured and the correlation between the CO₂ and the aerosol concentration can be used for analytical investigations, which use the measured CO₂-concentration to calculate a likely aerosol concentration. (*TU Berlin*)
- A longer stay in small, bad or not ventilated room can increase the probability of a Covid-19 spread by aerosols even on bigger distances over 2 m. (*RKI*)
- The use of our CO₂-sensors and the resulting room ventilation **helps minimizing the risk of infection** e.g. in schools or offices, gyms, restaurants or other premises where several people stay together.

Order numbers

■ müller	
GS 40.00 pro	CO ₂ - / air quality sensor (0-10 V)

0-10V SENSORS



Air quality sensors GS 40.00 pro

Order information

	EAN	Art. No.
GS 40.00 pro	4022709243317	24331
GS 40.00 pro RAL9005 jet black	4022709243218	24321

Technical data

Supply voltage	24 V ACDC
Sensors	CO ₂ Temperature Relative humidity Atmospheric pressure Dew point
Measuring range CO ₂ -concentration	390-5.000 ppm
Measuring range temperature	0°...+50° C
Measuring range relative humidity	0...100%
Measuring range atmospheric pressure	300-1.100 hPa
Outputs	3x analogue outputs (0-10 V)
Analogue measurement output	Temperature: 0 - 50° C Relative humidity: 0 - 100% Carbon dioxide CO ₂ : 0 - 2000 ppm
Permitted ambient temperature	0°...+50° C
Housing	self-extinguishing thermoplastic
Dimensions	80,5 x 80,5 x 17 mm
Housing color	studio white (similar to RAL 9016) or jet black (similar to RAL 9005) Specific colors on request
Mounting	Wall mounting (preferably combined with flush-mounting box)
Type of connection	Push-in connector
Type of protection	IP 20 (DIN EN 60529)
Class of protection	III when installed according to regulations



Functions and data provided to Modbus:

CO ₂	Value output
Relative humidity	Value output
Temperature	Value output
Dewpoint	Value output
Air pressure	Value output
and much more...	

Rights to technical amendments reserved / Technische Änderungen vorbehalten
Droits de modifications techniques réservés / Suscettibile di errori e modifiche