

ELAPSED TIME COUNTERS

müller BW 30.18



Retaining clip for Bx
30

Overview

- Front panel 53 x 28 mm
- Integral locking spring
- With universal connections
- Touch proof connections to VBG4
- Mounting aperture: 50 x 25 mm

Supply voltage versions

- see technical data

Order numbers

■ müller

BW 30.18

AC / Front 53x28mm

BG 30.18

DC / Front 53x28mm

ELAPSED TIME COUNTERS

müller BW 30.18

Order information

	Voltage	EAN	Art. No.
BW 30.18	230 V 50 Hz	4022709203069	20306
Other supply voltage versions on request			

Technical data BW 30.18 Alternating current

Voltage tolerance	±10%
Power consumption (real power)	0,11 W
Counter capacity	99.999 h.
Accuracy of reading	0,01 h.
Numeral height	4,4 mm
Numeral colour	white, decimal figures red
Operation indicator	fast-running wheel
Permitted ambient temperature	−15...+50 °C
Housing	self-extinguishing thermoplastic
Mounting	Panel
Type of connection	Universal: Screw, soldered and 6.3 x 0.8 mm AMP plug-type connections
Type of protection (DIN EN 60529)	Front IP 65
Class of protection	II when fitted in accordance with regulations

Rights to technical amendments reserved / Technische Änderungen vorbehalten
Droits de modifications techniques réservés / Suscettibile di errori e modifiche

