

WIRELESS SENSORS AND TRANSMITTER

Temperature sensor with ext. probe paladin 673 310 rf



Overview

- Sensor / transmitter with external temperature probe (3 m)
- Measuring range -20°C...+55°C
- Transmission intervall of temperature value: 1 / min.
- RF-repeater function included
- Compact housing
- Flush-mounted fitting
- Protection degree IP 20
- KNX-RF compatible

Order numbers

■ **paladin**

673 310 rf Temperature sensor with
ext. probe

WIRELESS SENSORS AND TRANSMITTER

Temperature sensor with ext. probe paladin 673 310 rf

Technical data

Supply voltage	230 V ~50 Hz
Transmission type	Codified transmission in 868,4 MHz with ERP>8 mW and a coverage of 100 m (in the free field)
Transmission cycle	1 min.
Compatible KNX-RF Commands	CC_Temperature
Measuring range temperature probe	-20°C...+55°C
Cable length temperature probe	3 m
Permitted ambient temperature	0°C...+45°C
Dimensions (sender)	46 x 42 x 13 mm
Mounting	Flush-mounting
Protection class (sender)	IP 20

Rights to technical amendments reserved / Technische Änderungen vorbehalten
 Droits de modifications techniques réservés / Suscettibile di errori e modifiche

