

AUDIO INTERFACES

müller AS 10.00 knx



Overview

- Buzzer for building automation KNX
- Up to 3 input objects can be configured
- Adjustable volume level (soft, medium, loud)
- Adjustable sequence
- Clearly structured ETS
- Easy handling and mounting
- Various mounting capabilities
- Compact housing

Order numbers

■ müller	
AS 10.00 knx	Buzzer

Accessories



Mounting plate for wall box 200.001



Mounting angle 200.002

AUDIO INTERFACES

müller AS 10.00 knx

Order information

	EAN	Art. No.
AS 10.00 knx	4022709240743	24074

Technical data

Supply voltage	via KNX bus voltage
Bus current	< 12 mA
Bus system	KNX
Volume level	soft (approx. 40 dB) medium (approx. 55 dB) loud (approx. 70 dB)
Tone sequence	continuous tone or adjustable sequence
Permitted ambient temperature	-10...+45 °C
Housing	self-extinguishing thermoplastic
Dimensions	55 x 55 x 12 mm
Housing color	studio white (similar to RAL 9016) specific colors on request
Mounting	wall mounting in frame (55x55mm) with mounting plate wall mounting with mounting angle
Type of connection	push-in connector according to DIN EN 60529:
Type of protection	IP X1 IP X4 when mounted with mounting angle
Class of protection	III when installed according to regulations

Rights to technical amendments reserved / Technische Änderungen vorbehalten
Droits de modifications techniques réservés / Suscettibile di errori e modifiche

